

Wallhung separation toilet, rimless
82066.2



TECHNICAL DATA

Order no.	82066.2
Certified to	EN 997
Specification	urine-diverting-toilet rimless Washdown for 4,5/3-l-flush (4/2,5-l-flush) Hygienic wastewater separation (installation in conjunction with Laufen installation system CW12 is required for the water drains). Odour trap in the urine siphon.
Outlet	horizontal
Weight	24,0 kg
Accessories excl.	Seat and cover, order no. 89395.5, 89695.0, 89896.5 Seat and cover with automatic lowering system, order no. 89160.1, 89395.9, 89695.1, 89896.6
Mounting acc. incl.	Urine siphon DN 32, sleeve DN 40, left or right, order no. 89866.9 laufen EasyFit system M12, order no. 89282.7

Mounting acc. excl.	Laufen installation system CW12, with cistern for wallhung separation toilet, order no. 82009.0 Stone screw fastening kit M12
Colours	see colour table

SPECIFICATION TEXT

Wallhung separation toilet rimless, washdown LAUFEN SAVE!, sanitary ceramic, for concealed frame with cistern for separation toilet (installation in conjunction with Laufen installation system CW12 is required for the water drains)
 EN 977, 4,5/3-l-flush (4/2,5-l-flush)
 dimensions 365 x 530 x 380 mm
 concealed trap, concealed fixation
 Special feature: hygienic wastewater separation, rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked
 Further options / accessories: Surface refinement LCC (only white), Laufen installation system CW12 for separation toilet, order no. 82009.0, WC seat and cover, 89395.5, 89695.0, 89896.5, WC seat and cover with automatic lowering 89160.1, 89395.9, 89695.1, 89896.6
 Order no. 82066.2

TECHNICAL DRAWINGS / S 1 : 20

