
INEO INSTALLATION SYSTEM

Installation element for wallhung bidet INEOLINK H917102



TECHNICAL DA	ТА	
Order no.	H917102	Ν
Certified to	EN 14055, EN 1519	_
matching for	Wallhung bidets	N
Specifications	Self-supporting steel frame for covering with	_
	plasterboard, installation onto a solid wall, in	
	drywall constructions.	
	Construction height 1120 mm.	Ν
	With support for ceramic with small contact	
	surfaces.	
	Non-slip leg supports, rotatable foot plates,	C
	height-adjustable 0-200 mm.	_
	Capable to resist 400 kg	
Installation depth	100-205 mm, wall bracket adjustable	_
	from 135-205 mm without tools	
Weight	12,0 kg	

Mounting acc. incl.	Fastening material, 2x M12 threaded rods for
	bidet fixation and drain elbow bracket.
Mounting acc. excl.	Commercially available wall disk 1/2".
	Angle valves and drain elbow DN 50.
	Sound insulation set,
	order no. VS16032 C00 000 0
Mounting information	Please note the necessary wall thickness of 80 mm
	in case of pre-wall installation.
Otherwise	Compatible with U-profiles UW 50, UW 75.
Colours	Surface powder coated

TECHNICAL DRAWINGS / S 1 : 20

