

INEO INSTALLATION SYSTEM

Installation element for urinal without integrated control INEOLINK H940101



TECHNICAL DATA

Order no.	H940101	Installation depth	100-205 mm, wall bracket adjustable from 135-205 mm without tools
Certified to	EN 14055, EN 1519	Weight	10,0 kg
matching for	Urinal ANTERO, order no. H841153 CAPRINO PLUS, order no. H841061 CASA, order no. H840145 IL BAGNO ALESSI, order no. H840975 LEMA, order no. H841193 TAMARO, order no. H840090 TARO-NOVA, order no. H840000 VAL order no. H840285 VILA order no. H841142	Mounting acc. incl.	Urinal inlet connection, concealed shell construction set with preliminary shut-off, building protection with cover, fastening material and 2x M8 threaded rods. Drain elbow and drain elbow bracket.
Specifications	Self-supporting steel frame for covering with plasterboard, installation onto a solid wall, in drywall constructions. Not suitable for urinals with a lid. Construction height 1120 mm. Non-slip leg supports, rotatable foot plates, height-adjustable 0-200 mm. Capable to resist 150 kg	Mounting acc. excl.	for Tamaro, Taro-Nova, order no. H89005 has to be used in combination with 1/2" connector H975113 Sound insulation set, order no. VS16032 C00 000 0
Water connection	left Rp 1/2, brass matching for standard pipe systems	Accessories excl.	Urinal flush plates Front plate INEO for manual control or front plate with infrared control
Flow pressure range	1-8 bar	Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation.
		Otherwise	Compatible with U-profiles UW 50, UW 75 and the Duofix*-System (*are registered third party trademarks)
		Colours	Surface powder coated

TECHNICAL DRAWINGS / S 1 : 20

